



### FLANGE DIMENSIONS, INCHES

VALVE SIZE	AWWA PRESS. CLASS	A	B	C	D	E	F	G	H	J	K	L	M1	M2	N	Q	ACT. SIZE	CYL. BORE
20	150	32.00	25.00	27.50	1.69	36.75	21.88	27.13	8.50	34.63	25.00	15.00	23.69	20.50	16.00	1.25	LS-5A	14
	300	34.00	27.00	30.50	2.50	37.38	25.13	30.38	8.50	37.88	25.00	15.00	25.75	22.71	17.00	1.38	LS-5A	14
24	150	37.00	29.50	32.00	1.88	43.13	26.25	31.50	8.50	39.00	28.25	15.00	27.44	23.77	18.50	1.38	LS-5A	14
	300	42.75	32.00	36.00	2.75	43.63	30.88	36.13	8.50	45.69	28.25	19.13	31.31	26.78	21.38	1.63	LS-5A	18
30	150	46.00	36.00	38.75	2.13	52.44	31.88	37.13	8.50	46.69	19.50	19.13	32.94	28.55	23.00	1.38	LS-5.2A	18
	300	50.25	39.25	43.00	3.00	53.44	37.25	42.50	8.50	52.06	19.50	19.13	37.50	31.99	25.13	2.00	LS-5.2A	18
36	150	54.00	42.75	46.00	2.38	62.00	38.13	43.38	8.50	52.94	19.50	19.13	39.13	33.85	27.00	1.63	LS-5.2A	18
	300	54.00	46.00	50.00	3.50	63.00	44.88	51.50	10.50	61.06	24.88	19.13	43.50	37.12	27.00	2.25	LS-6A	18
42	150	59.50	49.50	53.00	2.63	71.06	43.75	48.88	8.50	58.44	19.50	19.13	44.81	38.80	29.75	1.63	LS-5.2A	18
	300	61.00	52.75	57.00	3.29	72.56	51.50	58.00	10.50	70.56	24.88	25.13	49.25	42.07	30.50	2.25	LS-6.2A	24
48	150	72.00	56.00	59.50	2.75	79.69	49.50	55.63	10.50	68.19	24.88	25.13	50.19	43.39	36.00	1.63	LS-6.2A	24
	300	76.50	60.75	65.00	4.00	81.19	58.38	67.00	14.00	79.56	32.25	25.13	55.38	47.72	38.25	2.25	LS-7.2A	24

AWWA FLANGED BALL VALVE WITH CYLINDER ACTUATOR

DATE 5-7-08

**VAL-MATIC**<sup>®</sup> VALVE AND MANUFACTURING CORP.

DRWG. NO.

VM-4120/LSC