



Valve & Equipment Corporation

Specializing in Valves & Valve Automation Since 1983!

Model 750-65

Level Control Valve with Bi-Level Electric Float



- Reservoir filling
- Very low supply-pressure
- Low noise generation
- Energy cost-critical systems
- Systems with poor water quality
- Reservoir outflow
- Distribution routing
- Sewerage "fill and flush" systems



The Model 750-65 Level Control Valve with Bi-Level Electric Float is a hydraulically-operated, diaphragmactuated, control valve that controls reservoir filling in response to an electric float switch signal, opening at pre-set low-level and shutting-off at pre-set high level.

The double-chamber actuated Model 750-65-B is powered to fully open and close even at very low pressure.

Features and Benefits

- Line-pressure driven – independent operation
- Bi-Level electric float switch
 - On/off service
 - Low cavitation damage
 - No hydraulic sensing tubes
 - Simplified float installation & setting
 - Suited to various float switches
- Solenoid controlled
 - Low power consumption
 - Normally Open or Normally Closed main valve
- Double chamber
 - Full powered closing
 - Low throttling noise
 - Non-slam closing characteristic
 - Protected diaphragm
- External installation
 - Easy access to valve & float
 - Less wear and tear
- In-line serviceable – easy maintenance