



**PRESSURE / TEMPERATURE RATINGS  
 WAFER AND GLOBE STYLE SILENT CHECK VALVES**

TEMP. DEG. F.	MAXIMUM NON-SHOCK WATER SERVICE PRESSURE							
	GRAY IRON		DUCTILE IRON		GRAY IRON		DUCTILE IRON	
	125 LB. CLASS		150 LB. CLASS		250 LB. CLASS		300 LB. CLASS	
	2" - 12"	14" - 42"	2" - 12"	14" - 42"	2" - 12"	14" - 42"	2" - 12"	14" - 42"
0 - 150°	200	150	300	250	400	300	500	400
200°	190	135	280	230	370	280	460	370
250°	*	*	270	220	*	*	440	355
TEST PRESSURE	300	230	450	375	600	450	750	600

\* DUCTILE IRON RECOMMENDED FOR HOT WATER SERVICE ABOVE 200° F.

Contact us for more information: Valve & Equipment Consultants, Inc. • Phone: 281-324-1500 • Email: [sales@valveandequipment.com](mailto:sales@valveandequipment.com)

Website: [www.ValveAndEquipment.com](http://www.ValveAndEquipment.com)

Revised 5-8-98

**PRESSURE TEMPERATURE RATINGS**

DATE 5-2-78



**VALVE AND MANUFACTURING CORP.**

DRWG. NO.

**SS-120**